

## M440

## Automatic hand dryer, built-in installation

1800W automatic hand dryer for installation in a partition wall. 100mm recess depth, allowing installation in narrow cavities.



Reference	Finish
M440-S	Brushed stainless steel
Features	
Finishes	Brushed stainless steel (S)
Dimensions	H579 x W382 x D117mm
Air speed	28m/sec
Air temperature	54°C
Drying time	15-17 seconds
Power	1800W
Voltage	230/240V
Frequency	50/60Hz
Current	7.5 - 7.8A
Electrical insulation	Class I
Protection rating	IP21
Weight	14.3kg
Noise level	71dB (at 1 metre)
Warranty	5 years

## Optional accessories

---

No optional accessories.

## Installation information

---

### Wall cut-out

The M440 is designed for flush mounting in a partition wall with a minimum depth of 100 mm. Cut a hole measuring H548 x W357 mm.

### Fixation

It is fixed either by screws that are concealed on the inside or by the clamping system integrated into the hand dryer.

### Planning for sanitary facilities

To avoid reflection issues, do not install the sensor directly opposite other tap/soap dispenser sensors, other infrared devices or reflective surfaces. The choice of other accessories and their finishes must also be taken into consideration as they may reflect light and interfere with the sensor. Particular care must also be taken with the positioning of light in the room, especially with sensors on devices that are directed downwards.

## Maintenance

---

For optimal maintenance of the stainless steel hand dryer, use a soft cotton cloth and moisten it if necessary. Never use products containing hydrochloric acid, formic acid, acetic acid or chlorine-based bleaching agents.  
Never use abrasive products or tools (scouring liquid, scouring pad, scratchy dish sponge, stainless steel ball, etc.).

## Standards

---

CE  
RoHS

## Related products

---

Tap	R360
Soap dispenser	S260

## Related documents

---

Installation manual [contact@duten.fr](mailto:contact@duten.fr)

Technical diagram

